Capicorda in ottone aperti
Brass uninsulated terminals

MASCHIO - MALE



Articolo passivato Type Brass	Articolo stagnato Type Tinned	Esecuzione Execution	Sezione mm² Section mm² (AWG)	Dimensioni Dimensions mm	Inch	W	L	E	Conf. pezzi Packing pcs.
BM **01180**	BM **01181**	sciolti/loose	0,5 ÷ 1 (20-18)	6,3x0,8	0,250x0,032	6,3	20,6	6,35	2000
BM **02180**	BM **02181**	bobina/reel		6,3x0,8	0,250x0,032	6,3	20,6	6,35	7000
BM **01280**	BM **01281**	sciolti/loose	1,0 ÷ 2,5 (18-14)	6,3x0,8	0,250x0,032	6,3	20,6	6,35	2000
BM **02280**	BM **02281**	bobina/reel		6,3x0,8	0,250x0,032	6,3	20,6	6,35	7000

MASCHIO - MALE

Fig. 1

Fig. 2

Fig. 3

Fig. 4

Fig. 5

Fig. 6

Articolo passivato Type Brass	Articolo stagnato Type Tinned	Presa Male mm	Inch	Larghezza piastra mm	Foro vite mm	Fig.	Conf. pezzi Packing pcs.
BM **01002**	BM **02002**	6,3x0,8	0,250x0,032	8	4,3	1	1000
BM **01005**	BM **02005**	6,3x0,8	0,250x0,032	8	4,3	2	1000
BM **01009**	BM **02009**	6,3x0,8	0,250x0,032	8	4,3	3	1000
BM **01011**	BM **02011**	6,3x0,8	0,250x0,032	8	4,3	4	1000
BM **01013**	BM **02013**	6,3x0,8	0,250x0,032	8	4,3	5	1000
BM **01014**	BM **02014**	6,3x0,8	0,250x0,032	8	4,3	6	1000

COPRIPRESA - SLEEVES

Fig. 1

Fig. 2

Fig. 3

Fig. 4

Fig. 5


Fig. 6


Fig. 1

Fig. 2

Fig. 3

Fig. 4

Fig. 5


Fig. 6

COPRIPRESA IN NYLON
Materiale: Poliammide (PA 6.6) naturale
Autoestinguenza: UL-94 V-2 IEC 695-2-1 a 850°C e IEC 695-2-2
Temperatura max. di esercizio: T 105°C
Massima tensione applicabile alle parti conduttrici: ⩽ V 450

COPRIPRESA IN POLIETILENE
Materiale: Polietilene (PE) colore naturale
Autoestinguenza: UL-94 HB
Temperatura max. di esercizio: T 60°C
Massima tensione applicabile alle parti conduttrici: ⩽ V 50

NYLON SLEEVES
Material: Polyamide (PA 6.6) natural color
Flammability: UL 94 V-2 IEC 695-2-1 to 850°C and IEC 695-2-2
Max working temperature: T 105°C
Max rated voltage applicable to the electrical conductors: ⩽ V 450

POLYETHYLENE SLEEVES
Material: Polyethylene (PE) natural color
Flammability to: UL 94 HB
Max working temperature: T 60°C
Max rated voltage applicable to the electrical conductors: ⩽ V 50

Articolo Type	Fig.	Materiale Material	Per capicorda For terminal mm	Inch	Conf. pezzi Packing pcs.
BM **01017***	1	Polietilene	Femm. 6,3	0,250	1000
BM **01022***	2	Nylon	Femm. 6,3	0,250	500
BM **01021***	3	Polietilene	Femm. 4,8	0,187	1000
BM **01023***	2	Nylon	Femm. 4,8	0,187	1000
BM **01020***	3	Polietilene	Femm. 2,8	0,110	1000
BM **01019***	4	Nylon	Femm. 2,8	0,110	1000
BM **01016***	5	Polietilene	Maschio 6,3	0,250	500
BM **01018***	6	Nylon	Femm. Bandiera 6,3	0,250	500

*Fornibili anche in versione di colore rosso e nero / Red and black color on request