elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET

ECTC1520

PLIABLE PVC CONDUIT 33212 Ø20 mm - 100 m

Tuberías y accesorios > Tubería > Tubos corrugados > Tc15 - pvc - 33212 > Tc15 - pvc - 33212 > Negro

Technical Symbols/Marks/Approvals

UL94 V0 | GWT 960° | CE | RoHS II | MADE IN ITALY

Estándares

EN 61386-1 EN 61386-22

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	**Material**	Polyvinyl chloride (PVC)	**Halogen free**	No
Colour	Black	**RAL-number**	9005	**UV resistant**	No
Suitable for underground installation	No	**Operating temperature**	-5-60 etim.un.eu570073.abb	**Bending strength**	Pliable
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	**Impact strength class according to EN 61386-1**	Medium (class 3 / 2 Joule)	**With sleeve**	No
Fire retardant version	Yes	**Surface mounting**	No	**Suitable for installation on wood**	No
Suitable for hollow wall installation	No	**Suitable for concrete installation**	No	**Machine and systems installation**	No
Suitable for underfloor installation (screed)	No	**Suitable for outdoor installation**	No	**Inner diameter**	13.6 etim.un.eu570448.abb
Outer diameter	20 etim.un.eu570448.abb	**High conducting inner coating**	No	**With metre indication**	No

Documentation available for download

Certification

IMQ_EM685_2023-01-20 TC15 AN.pdf

Certification

Tubo corrugato IMQ_EN836_2023 AV.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8054320282167
Cardboard
100 MT
0.58x0.58x0.18 [m]
5.8 [kg]

barcode

8056351663052
Pallet
5200 MT
0.8x1.2x2.5 [m]
301.6 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.